

YAMAMOTO COINLAUNDRY

DRY

WASH&DRY

WASH&DRY

WASH

How to Use

1. Please be careful not to put too much laundry ...
2. Please check the inside of your pocket before washing ...
3. Please be careful about the drying time for synthetic fibers ...
4. Blankets cannot be washed in a small washing machine ...
5. Do not leave the laundry after the operation is completed ...
6. It is prohibited to use the ones used by patients with infectious diseases ...



Plasmacluster Ion device as standard

Installed Plasmacluster ion device for sterilization and static reduction effect

Point 1

Plasmacluster sterilizes during drying phase

Point 2

Static reduction effect suppresses the crackle when taking out the garments.



WASHER & DRYER WD-CS SERIES

FEATURES

Improved various functions

- Easy to set program
- High-visibility screen with large character display
- Industry-leading extracting rotation reduces gas consumption
- Duct structure prevents jamming lint
- Easy access to drain valve

DRYER VG-C/CW SERIES

FEATURES

Added various functions

- Concentrated duct from model VG142CW
- New released large dryer VG352C can be differentiated from other stores.

WASHER WN-CS SERIES

FEATURES

Improved various functions

- Installed user-friendly touch screen
- Easy to set program
- High-visibility screen with large character display
- Easy access to drain valve

Cion laundry machines specification data

Wash & Dry combo

Type	WD-CS			
Color				
	[Stainless panel(OP)] [White panel]			
Model	WD120CS	WD172CS	WD272CS	WD352CS
Dimension	●Wash capacity.....12kg ●Dry to dry capacity.....8kg			
Drum	Diameter ϕ 600mm			
	Depth 450mm			
Drum rotating speed	Wash 50min-1			
	Extraction 772min-1			
Power supply	3 Phase, AC200V	3 Phase, AC200V	3 Phase, AC200V	3 Phase, AC200V
Circuit breaker	10A	20A	30A	30A
Power consumption	670W	1150W	1710W	1850W
Motor	Drive motor 1.5kW 4P			
	Fan motor 0.4kW 4P			
Water supply connection	20A	20A	20A	20A
Hot water supply connection (Option)	20A	20A	20A	25A
Drain connection	65A	65A	65A	65A
Gas connection	15A	15A	15A	15A
Gas type	LPG · City gas 13A	LPG · City gas 13A	LPG · City gas 13A	LPG · City gas 13A
Gas consumption	14kW	14kW	23.3kW	27.9kW
Duct diameter	ϕ 200mm	ϕ 200mm	ϕ 200mm	ϕ 200mm
Exhaust air volume	7.8m3/min	7.6m3/min	16.7m3/min	24.4m3/min
Dimension	W 804×D1,119×H1,794mm	W867×D1,156×H1,794mm	W1,008×D1,352×H1,813mm	W1,145×1,417×H1,943mm
Weight	510kg	618kg	864kg	1,080kg
Max preinstalled pump	6 units	6 units	6 units	6 units

Dryer

Type	VG		
Color			
	[Stainless panel(OP)] [White panel]		
Model	VG142C	VG142CW	VG252C
Dimension	●Capacity.....14kg		
Drum	Diameter ϕ 760mm	Diameter ϕ 760mm×2	Diameter ϕ 900mm
Drum rotating speed	43min-1	43(50Hz) 42(60Hz) min-1	38min-1
Power supply	3 Phase, AC200V	3 Phase, AC200V	3 Phase, AC200V
Circuit breaker	15A	10A×2	20A
Power consumption	430W	380W×2	820W
Motor	Drive motor 0.2kW 4P		
	Fan motor 0.4kW 4P		
Gas connection	15A	15A×2	15A
Gas type	LPG · City gas 13A	LPG · City gas 13A	LPG · City gas 13A
Gas consumption	18.6kW	18.6kW×2	27.9kW
Exhaust duct diameter	ϕ 200mm	ϕ 200mm	ϕ 200mm
Exhaust air volume	12(50Hz) 15(60Hz) m³/min	2段同時 24(50Hz) 27(60Hz) m³/min	17(50Hz) 20(60Hz) m³/min
Dimension	W810×D1,089×H1,589mm	W810×D1,243×H1,990mm	W970×D1,292×H1,889mm
Weight	235kg	415kg	375kg

Washer

Type	WN-CS		
Color			
	[Stainless panel(OP)] [White panel]		
Model	WN132CS	WN232CS	WN282CS
Dimension	●Wash capacity.....13kg		
Drum	Diameter ϕ 660mm	Diameter ϕ 762mm	Diameter ϕ 890mm
Drum rotating speed	Wash 42min-1	Wash 40min-1	Wash 40min-1
Extraction	950min-1	880min-1	800min-1
Power supply	3 Phase, AC200V	3 Phase, AC200V	3 Phase, AC200V
Circuit breaker	15A	20A	30A
Power consumption	1,140W	1,470W	1,680W
Motor	2.2kW 4P	3.7kW 4P	3.7kW 6P
Water supply connection	20A	25A	25A
Hot water supply connection (Option)	20A	25A	25A
Drain connection	65A	65A	65A
Dimension	W863×D1,029×H1,504mm	W1,008×D1,207×H1,506mm	W1,143×D1,277×H1,656mm
Weight	500kg	740kg	940kg